



Combi-15-Flexi

- 2 x Flexi-8
- 2 x Ventus-15
- Verstärker Empfehlung:
- Powersoft T604, 4 x 1.250 W/8 Ω, 4 x 1.500 W/4 Ω

Combi-15sp-Flexi

- 2 x Flexi-8
- 1 x Ventus-15
- 1 x Ventus-15sp

Flexi-8

Frequenzgang	65 Hz - 23 kHz (- 10 dB) 90 Hz - 22 kHz (+/- 3 dB)
Abstrahlverhalten	asymmetrisch 100° bis 50° x 55°
Belastbarkeit	200 W AES / 400 W program / 800 W peak at 8 Ω
Schalldruck	116 dB SPL AES / 119 dB SPL program / 122 dB SPL peak
Komponenten	LF: 1 x 8" Tiefmitteltöner HF: 1 x 1" Kompressionstreiber
Anschlüsse	2 x Neutrik NL4 Speakon IN/OUT (durchgeschliffen), Belegung: 1+/1-
Maße	474 (H) x 258 (B) x 282,2 mm (T)

Ventus-15/15sp

Untere Grenzfrequenz	34 Hz (- 10 dB) 43 Hz (+/- 3 dB)
Belastbarkeit	1.000 W AES / 2.000 W program / 4.000 W peak an 8 Ω
Schalldruck	127 dB SPL AES / 130 dB SPL program / 133 dB SPL peak
Komponenten	1 x 15" Tieftöner mit 4" Schwingspule
Anschlüsse	2 x Neutrik NL4 Speakon IN/OUT (loop through), configuration: 2+/2-
Maße	438 (h) x 580 (w) x 540 mm (d)
Endstufe	4.6 kW, dreikanalig
Verstärkerleistung CH1	2.600 W/ 8 Ω, 2.200 W/ 4 Ω
Verstärkerleistung CH2 & CH3	750 W/ 8 Ω, 1.000 W/ 4 Ω, 750 W/ 2 Ω

