



## Combi-15-Axon

2 x Axon-12x3

2 x Ventus-15

Verstärker Empfehlung:

Powersoft T604, 4 x 1.250 W/8 Ω, 4 x 1.500 W/4 Ω

## Combi-15sp-Axon

2 x Axon-12x3

1 x Ventus-15

1 x Ventus-15sp

## Axon-12x3

<b>Frequenzgang</b>	100 Hz - 16 kHz (- 10 dB) 140 Hz - 14 kHz (+/- 3 dB)
<b>Abstrahlverhalten</b>	80° x 20°
<b>Belastbarkeit</b>	240 W AES / 480 W program / 960 W peak at 12 Ω
<b>Schalldruck</b>	119 dB SPL AES / 122 dB SPL program / 125 dB SPL peak
<b>Komponenten</b>	12 x 3" Breitband Chassis
<b>Anschlüsse</b>	2 x Neutrik NL4 Speakon IN/OUT (durchgeschliffen), Belegung: 1+/1-
<b>Maße</b>	1.034,5 (H) x 115 (B) x 145 mm (T)

## Ventus-15/15sp

<b>Untere Grenzfrequenz</b>	34 Hz (- 10 dB) 43 Hz (+/- 3 dB)
<b>Belastbarkeit</b>	1.000 W AES / 2.000 W program / 4.000 W peak an 8 Ω
<b>Schalldruck</b>	127 dB SPL AES / 130 dB SPL program / 133 dB SPL peak
<b>Komponenten</b>	1 x 15" Tieftöner mit 4" Schwingspule
<b>Anschlüsse</b>	2 x Neutrik NL4 Speakon IN/OUT (loop through), configuration: 2+/2-
<b>Maße</b>	438 (h) x 580 (w) x 540 mm (d)
<b>Endstufe</b>	4.6 kW, dreikanalig
<b>Verstärkerleistung CH1</b>	2.600 W/ 8 Ω, 2.200 W/ 4 Ω
<b>Verstärkerleistung CH2 &amp; CH3</b>	750 W/ 8 Ω, 1.000 W/ 4 Ω, 750 W/ 2 Ω

